

LIFEBOOK S6410

Get ready for your next business trip

Issue June 2008

Pages 4

The exclusive LIFEBOOK S6410 is your best friend on the move, leaving no compromises!

The sturdy notebook keeps the balance between low weight, best connectivity, high-end performance and modularity. With its integrated UMTS/HSUPA, ConfCamera and brilliant 13.3-inch wide display, you are going to experience true mobility – anywhere, anytime.

The combination of performance, modularity and flexibility gives you the functionality and ease of use of a full-sized PC. Intel® Centrino® Duo Mobile Technology with latest Intel® GM965 chipset technology delivers high performance and Business-day-long independency from the power socket.

This notebook is designed for highest quality with extensive testing and an extra-strong magnesium lid.

Elegance

Designed for the most demanding mobile users, LIFEBOOKs are the perfect synthesis of form, function and style.

- Light-weight modular 13.3-inch wide notebook with only 1.7 kg
- Exclusive protective leather bag
- Modular bay fitting an optical disk drive or battery
- Excellent resolution and video quality

Ergonomics

- 13.3-inch WXGA -display for maximum viewing comfort
- Convenient working with full sized keyboard
- Small in size but great expandability with maximum ports
- Eco Button to extend battery life by powering down energy consumption

Connectivity

- Bluetooth and Wireless LAN optional integrated
- Optional Port Replicator for easy connection to all your peripherals, compatible with LIFEBOOK E Series and LIFEBOOK C Series
- Long lasting battery for Business-day long independency with first and second battery

Security

- Trusted platform module (TPM 1.2) provides more secure applications and makes transitions safe
- Biometric fingerprint sensor
- Built-in SmartCard controller and optional SmartCase Logon+: software with best integration into your IT environment
- Lock workstation Button for fast sign off the system

Reliability

- Highest quality design with magnesium lid
- Hard disk drive ShockSensor minimizes data loss and guarantees a higher reliability of your data
- Spill-proof keyboard offers protection against system damage

Manageability

- Integrate the bundled system management software Desk View Admin in every common IT infrastructure
- Seamless integration in heterogeneous enterprise management systems
- Get optional add on packages: With DeskView Migrate and DeskView Control for e.g. migration projects and extensive client lifecycle management tasks



System	LIFEBOOK S6410
Processor	
Intel® Core™2 Duo Processor	T8100 (2.1GHz) T8300 (2.4GHz)
Second level cache	3 MB
Front side bus (FSB)	800Mhz
Intel® Core™2 Duo Processor	T9300 (2.5GHz) T9500 (2.6GHz)
Second level cache	6 MB
Front side bus (FSB)	800Mhz
Chipset	
Northbridge	Intel® GM965
Southbridge	ICH 8-M
Memory	
DIMM slots	2
DDR2-667 SDRAM, 667 MHz	up to 4GB
BIOS	
BIOS Flash EPROM	BIOS based on Phoenix TrustedCore Notebook
Interfaces	
SIM card slot	1
Infrared link (Fast IrDa 1.1, 4 Mbps)	1
Type I/II PC Card slot	1
Memory card slot (SD, MS, xD and MSPRO)	1
USB 2.0	3
S-Video out (TV-out) without adapter cable	1
VGA	1
Modem RJ-11	1
LAN RJ-45	1
Audio-in (line-in / microphone)	1
Audio-out (line-out / headphone)	1
DC-in	1
IEEE1394	1
Kensington Lock	1
Docking connector for Port Replicator	1
Port Replicator interfaces (optional):	
USB 2.0	4
VGA	1
DVI-D	1
Serial port	(with HDCP support)
Parallel port	1
LAN RJ-45	1
PS/2	1
DC-in	1
Microphone	1
Headphone	1
Power on switch	1
Kensington Lock	1
Camera	Built-in ConfCamera (1,3 megapixel VGA Camera)
Modem on board	
56K V.92 modem MDC1.5	1
LAN on board	
built-in 10/100/1000 Mbps Marvell 88E8055	x
Wireless Technologies (WLAN)	
Import and usage according to country-specific regulations.	
3 Dual band WLAN antennas, 2 UMTS antennas	
Intel® Wireless WiFi Link 4965AGN	optional
Atheros Minicard b/g 802.11 b/g	optional
WiFi certified	x
Integrated UMTS/HSUPA, also supported are GPRS and EDGE or higher	Optional (downlink 7.2, uplink 2.0)
Bluetooth	
Bluetooth V2.0	optional
Audio	
Stereo speakers	x
Sound chip	RealTek ALC262
Internal microphone	2
Keyboard and pointing device	
Keyboard	Spill proof keyboard, 85 keys, 19mm pitch, 3mm key stroke
Touchpad	with two mouse buttons, scroll via fingerprint sensor
Fingerprint sensor	x
Launch Keys	
Application Buttons	4
Lock workstation Button	x
Mobility Center Button	x
Eco Button	x
Recovery Button	x
Status LED	x
Graphics	
Intel® X3100 integrated graphics	x
Direct X9	x
Direct X10	x (Q4/2007)
Pixelshader 3.0	x
Pixelshader 4.0	x (Q4/2007)

DualView (Windows XP & Windows Vista)	x
Display 13.3-inch TFT WXGA /1280 x 800 pixel, glare display Max. resolution for external displays	x 1920 x 1200 / true color / 60 Hz (tbd.)
Hard disk drives (internal) * S.M.A.R.T. ShockSensor for HDD shock protection 80 GB S-ATA 150 (5400 rpm) 120 GB S-ATA 150 (5400 rpm) 160 GB S-ATA 150 (5400 rpm) 160 GB S-ATA 150 (7200 rpm) 64 GB Solid State Disk * 1 Gbyte equals one billion bytes, when referring to hard disk drive capacity; accessible capacity may vary, also depending on used software and tool.	x x x x x x
Modular Drives DVD super-multi drive incl. RAM More information in specific Data Sheet: http://www.fujitsu-siemens.com/optical_drives/	x
Manageability	
Please refer to http://www.fujitsu-siemens.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html Supported Standard WMI / CIM / WBEM PXE BootP	x x made4you
Security Physical security Kensington Lock support System Security Boot sector virus protection Trusted Platform module 1.2 Symantec Norton Internet Security User Security User and supervisor BIOS password SystemLock BIOS SmartCard security Hard disk password Integrated Fingerprint Sensor Integrated SmartCard controller in PC Card with system lock support SmartCase Logon+ incl. Fingerprint Software	x - optional x x x x x x x
Power supply 1st Li-Ion battery 6 cell 5200mAh (53.3 Wh) 2nd Li-Ion battery 6 cell 2300mAh (24.8Wh) (Option) First battery * (Mobile Mark 2005) [up to] First + Second battery * (Mobile Mark 2005) AC adapter 19V/80W Adapter Rated voltage (AC input) 100 - 240 V Rated frequency 50 - 60 Hz DC output 19 V, 4.22	optional 8 h 11.4 h x
Operating temperatures Relative humidity (non-condensing) Ambient temperature	20% - 85% (running) 5° - 35° C
Dimensions / Weight Dimensions (H x W x D) Weight* * Weight may vary depending on actual configuration	314 x 234 x 22.7 – 31.5 mm 1,75 kg
Certificates CE Marking CE according to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE according to 99/5/EEC (R&TTE) CE! (Wireless) CE (Emission/Immunity) R&TTE FCC GS (German ergonomic approval) UL/cUL CB Generic Report CB (Safety) RoHS WHQL TBR21 Energy Star WiFi certified	x x x x (with integrated WLAN) x x - tbd x x x x x x x x
Operating System Microsoft Windows XP Professional Microsoft Windows Vista™ Microsoft Windows Vista® Business/ Microsoft Windows XP® Professional TwinLoad	driver support x x
Software (compatibility / preinstalled) Adobe Acrobat Reader Application panel tool Camera Windows Vista recovery media Driver and Utility DVD (DUDVD) Eco Power Saving Utility	x x x optional (extra order number) optional (extra order number S26361 F2007 E903) x

Easy Guide on-line user documentation	x
Nero Essentials	x
Norton Internet Security (incl. Firewall) on DUDVD for Microsoft Windows XP	x
SmartCase Logon+	x
Toshiba Bluetooth Stack	x
UMTS watcher	optional with UMTS
DVD playback software	optional
Accessories (order number)	
AC-adapter	S26391-F408-L300
Case	S26391-F119-L57
Port Replicator	S26391-408-L100
Battery	1st: S26391-F405-L820 2nd: S26391-F405-L821
Modem adapter set 1: D, UK	S26391-F3145-L10
Modem adapter set 2: SW, NO, FI, DK	S26391-F3145-L20
Modem adapter set 3: CH, A, B, NL, F, I, E, POR	S26391-F3145-L30
http://www.fujitsu-siemens.com/accessories/	
Spare part availability	5 years